U.T. Administration of Daman & Diu, (Police Department) Daman FAX No. 0260 - 2220026

No. ASD/DMN/PMS/UPS /2012/

Dt.30/03/2012

SHORT TERM QUOTATION NOTICE

Sealed Quotations are hereby invited by the undersigned on the behalf of the President of India from the interested manufacture/Authorized Dealers/Suppliers for the following type of Fiber Lathi under PMS so as to reach by Register Post/ Courier/ Hand Delivery of before 16/04/2012 up to 15:30 hrs.

| Sr. No. | Particulars | Qty | Rate per No. |
|---------|------------------|---------|--------------|
| 1. | UPS for Computer | 25 Nos. | |

Terms and Conditions: -

- The sealed envelope should be super scribed by words "Quotations for" UPS for Computer.
- The rates should be quoted inclusive of all taxes and fright charge for Daman Police H.O. Daman only.
- 3. Quotation received after due date and time will not be taken into consideration.
- Complete details in all respect of UPS for Computer for Police Department should be produced with rate quotation notice.
- The E.M.D. of Rs. 2500/- in form of FDR/SD from of any Nationalized of Schedule Bank in favour of the Dy. Inspector General of Police, DD, Daman should be attached with sealed quotation & Demo Training at Nani Daman Police Station.
- Payment will be made only after execution of purchase order as per this
 Department's specification
- On acceptance of rates complete UPS for Computer in all respect should be delivered within stipulated period from the date of supply order.
- Item of UPS for Computer should be of standard quality only. The substandard materials shall be rejected.
- 9. If any **UPS for Computer** found defective it should be replaced by the supplier at his own risk & cost.
- 10. Quotation without EMD/SD will not be considered.
- The Supplier/Manufactures must have SST/CST registration with Govt.
 Department Concerns.
- 15. Right to reject or accept any or all quotations is reserved with the undersigned.
- 16. The quantity can be increased/decreased subjects to budgetary provisions.
- Supplier will be required to produce sample / demonstration on the due date of Opening of the quotation.

Addl. Supdt. of Police, Daman and Diu, Daman.

1.Copy to all Suppliers/Firms

2. Copy fd. wcs. to the All Head Officer, Daman for wide publicity please.

3. The NIC, Daman, with request to display the above said notice on Police Department Website for wide Publicity please

8 hour(s) recharge time Included Battery Modules **RBCTM** Quantity Replacement Battery Communications & Management Interface **USB** Port(s) Multi-function LCD status Control panel and control console Alarm when on battery: distinctive low battery alarm: Audible Alarm overload continuous tone alarm Surge Protection and Filtering Surge energy 355 Joules rating Analog phone line for phone/fax/modem/DSL (RJ-45 connector), Network line -10/100 Base-T Ethernet (RJ-Data Line 45 connector), Coaxial cable Protection CATV/SATV/modem/Audio-Video (coax connector) Filtering Physical Maximum 250.00 mm Height Maximum 100.00 mm Width Maximum 382.00 mm Depth 11.36 KG Net Weight Shipping 12.34 KG Weight Shipping 337.00 mm Height Shipping Width 225.00 mm

Typical

| Technical Spec | ifications |
|-----------------------------|--------------------------------------|
| Output | |
| Output Power | 1000 VA |
| Capacity | 1000 VA |
| Nominal | 100V |
| Output Voltage | |
| Efficiency at | 78.0% |
| Full Load | |
| Output | 50/60 Hz +/- 3 Hz user adjustable |
| Frequency | +/ 0.1 |
| (sync to mains) Waveform | |
| Type | Stepped approximation to a sine wave |
| Type | |
| Outmut | (4) NEMA 5-15R (Battery Backup) |
| Output Connections | |
| Connections | (4) NEMA 5-15R (Surge |
| T.CC . | Protection) |
| Efficiency at | 84% |
| Half Load | Duilé in Donner |
| Bypass Max | Built-in Bypass |
| Configurable | 45.00 dBA |
| Power | |
| Input | |
| Nominal Input | |
| Voltage | 100V |
| Input | 50/(011 1/ 211 / |
| Frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input | Japanese 2-pin |
| Connections | NEMA 5-15P |
| Cord Length | 1.83 meters |
| Input voltage | 1.05 meters |
| range for main | 83 - 122V |
| operations | |
| Maximum | 124 |
| Input Current | 12A |
| Input Breaker | 15.0 A |
| Capacity | |
| Batteries & Ru | |
| | Maintenance-free sealed Lead- |
| | Acid battery with suspended |
| | electrolyte : leakproof |

Shipping Depth 487.00 mm Color Black Units per Pallet 32.00 Pallet Weight 393.28 KG Master Carton Units SCC Codes Environmental Operating 0 - 40 °C Environment Operating Relative 0 - 95% Humidity Operating 0-2952.6 meters Elevation Storage Relative 0 - 95% Humidity Storage 0-14763.6 meters Elevation Audible noise at 1 meter from 45.00 dBA surface of unit Storage Temperature Online Thermal Dissipation

> Addl. Supdt. of Police Daman